65’’ (64.5” viewable) Full HD LED Commercial Display

CDE6502



The ViewSonic® CDE6502 is a 65’’ (64.5” viewable) Full HD commercial display with 1920 x 1080 resolution, 350-nit brightness, wide viewing angles and dual 10W speakers, providing high-impact messaging in hotels, restaurants, and other businesses. In addition to HDMI and VGA inputs to connect with various high definition devices, the display utilizes an integrated quad-core processor and 8GB of internal memory, allowing customers to playback multimedia content via USB or web browsing through RJ45 connectivity without the need for a PC. To make life even easier, the bundled vController software offers easy maintenance and intuitive interfaces for remote management via a PC server or laptop, and its flicker-free and blue light filter technologies help provide a comfortable viewing environment.

- Advanced media player
- Integrated USB multimedia playback
- Quad-core processor and RJ45 connectivity
- Free bundled vController software
- Control multiple devices with HDMI CEC and IR pass-through
- Enhanced viewing comfort

Advanced media player

Integrated customized Android-based media player, the display provides flexible content loading

options and web browsing via LAN connectivity, without the need of an external media player or a PC.



USB Multimedia Playback

This display features a convenient USB multimedia playback function. Now photos, music, and 1080p video can be quickly displayed on-screen directly from a USB drive.



Quad-core Processor and RJ45 Connectivity

Featuring a powerful quad-core processor and RJ45 connectivity, this display offers convenient web browsing functionality. Users can search online and watch videos directly on the display without having to connect to other computing devices. The RJ45 connectivity also provides intranet and wireless capabilities when connecting to a wireless router.



Free Bundled vController Software

Included vController software provides a simple and intuitive interface for remote management, OSD-related settings, and scheduling on deployed displays through RS232 or LAN.



Control Multiple Devices

RS232 IR pass-through offers local control for set-top boxes, and other RS232 connected devices, directly with the display’s remote controller.

HDMI CEC functionality offers local control of DVD players, sound systems, and other HDMI connected devices, directly with the display’s remote controller.



Enhanced Viewing Comfort

Flicker-Free technology and a Blue Light Filter help to eliminate eye strain from extended viewing periods.



Dual Integrated Speakers

Designed with dual integrated speakers, this display combines incredible screen performance with stereo sound for an immersive multimedia experience.



Technical Specifications

LCD PANEL	Panel Size	65''
	Type/ Tech	TFT LCD Module
	Display Area (mm)	1428.48 (H) x 803.52 (V) (65” diagonal)
	Aspect Ratio	16:9
	Resolution	1920 x1080
	Colors	1.07 Billion colors
	Brightness	350 nits (typ.)
	Contrast Ratio	4000:1 (typ.)
	Response Time	8 ms
	Viewing Angles	H = 178, V = 178 (typ.)
	Backlight	LED Backlight
	Backlight Life	30,000 Hours (typ.)
	Hardness	N/A
TOUCH	Type/ Tech	N/A
	Touch Resolution	N/A
	Touch Point	N/A
	Response time	N/A
	System	N/A
	Life time	N/A
INPUT	HDMI	x 2 (1 support MHL)
	RGB / VGA	x1
	DisplayPort	N/A
	DVI	N/A
	RF (TV)	N/A
	Audio	x1 (3.5mm jack)
	CVBS	N/A
	YPbPr	N/A
	MIC(Microphone)	N/A
	RS232	x1
	SD/SDHC	N/A
	OPS	N/A
OUTPUT	RGB / VGA	N/A
	DisplayPort	N/A
	DVI	N/A
	Audio	x1 (3.5mm jack)
	CVBS	N/A
	YPbPr	N/A

	SPIDF	N/A
	RS232	N/A
	Remote Control	N/A
	IR Pass Through	N/A
LAN	RJ45	x1
USB	Type A	x3 (USB3.0 x2)
	Type B	N/A
	Mini USB	N/A
	Micro USB	N/A
SPEAKERS		10W x 2
BUILT-IN PC	Processor	Quad Core
	Graphic	N/A
	Sound card	N/A
	Memory	2GB
	Storage	8GB
	Networking	N/A
COMPATIBILITY		
	RGB PC/HDMI PC	480i, 480p,720p,1080i,1080p
	CVBS	N/A
	S-Video	N/A
	YPbPr	N/A
	HDMI	480i, 480p,720p, up to 1080p
	DVI	N/A
CONTROLS	Physical- Top OSD	Picture:Picture Mode, Contrast, Brightness, Hue, Sharpness, Saturation, Anti-Flicker, Backlight, Clock, Phase, Horizontal Position, Vertical Position, Auto Tune, Color temperature, Bluelight Filger, Zoom Mode, OverScan, Image NR, MPEG NR Sound: Sound Mode, Bass, Treble, Balance, Surround, Alone Setting: Source auto switch, MHL Auto Switch, Movie Mode, Menu Timeout, Date/Time, Off Timer, On Timer, Sleep Time Lock: Lock System, Set Password, Block Program, System ID, Lock Keypad, Restore To Default
	Embedded Linux OS	N/A
	Multimedia	N/A
POWER	Voltage	100-240 VAC +/- 10% Wide Range, 50-60Hz +/-3 Hz
	Consumption	"On": Max 180 W, 150 W(Default) "Off"(Suspend): ≤ 0.5 W
ERGONOMICS	Tilt	N/A
	Wall Mount (VESA®)	400x400mm ; Screw: M8*15 mm

OPERATING CONDITIONS	Temperature (º C)	32°F to 104°F (0°C to 40°C)
	Humidity	20% ~ 80% non-condensing
DIMENSIONS (W x H x D)	Physical w/ stand (inch / mm)	59.53 x 39.53 x 11.81 / 1512 x 1004 x 300
	Physical w/o stand (inch / mm)	59.53 x 34.96 x 3.43 / 1512 x 888 x 87
	Packaging (inch / mm)	63.70 x 40.83 x 8.78 / 1618 x 1037 x 223
WEIGHT	Net w/ stand (lb / kg)	121.25 / 55
	Gross (lb / kg)	125.67 / 57 (w/o stand)
REGULATIONS	Standard	cTUVus, FCC, Energy Star 7.0, Mexico Energy, CE, CB, RoHS, ErP, WEEE
WARRANTY		**Warranty offered may differ from market to market
What's in the box?		1.CDE6502 commercial display 2.Remote Control with batteries 3.User manual CD wizard 4.Quick Start Guide 5.Power Cables *Actual content may differ from market to market

ViewSonic® Limited Warranty

ViewSonic provides customers with the security of a manufacturers warranty against defected products. The type and duration of the applicable warranty service varies by product type, country of purchase and can also vary on an individual basis according to customer requirements agreed at time of purchase. The warranty will expire after the end of the warranty period.

For more product information, visit us at **www.viewsoniceurope.com**

All rights reserved by ViewSonic Corporation. All other Corporate names and trademarks are the property of their respective companies. E&EO. All prices and specifications are subject to change without written notice. Images are for illustrative purpose only. Terms & Conditions Apply.