ViewSonic

PROJECTOR
PS750HD


Key **Features**

A Total Solution for School Projection | 10-point Touch Collaboration | Wide Area Laser Detection | One Account Wherever You Go | Cloud Storage Service



Product **Description**

The ViewSonic PS750HD projector is a total solution for school projection, complete with interactive modules, wall mount kit and digital white board software. With the ability to project 100” images from a distance of only 0.15m* from the projection surface, the projector is flexible enough to fit any classroom installation by keeping the projection beam out of sight and eliminating image shadows for distraction-free classroom application. A customisable wall mount with quick installation and flexible adjustment features a 3-axis alignment system. The interactive module supports and recognises finger touch, allowing users to work on projected images collaboratively. vBoard for Windows digital whiteboard software offers access to rich interactive teaching tools and allows teachers to take entire lessons from classroom to classroom with ease via a MyViewBoard.com account. Vertical projection is perfect for starting group discussions, making subjects more immersive, and allowing multiple students to collaboratively draw and write on the same flattop screen. Utilising PS750HD’s cleverly concealed PortAll™ compartment guarantees more flexibility when using wireless dongles and PC sticks, and allows teachers to present their own customised lesson content. PS750HD is the ultimate complete-package interactive projection solution for school projection and the perfect fit for making class more engaging than ever.
*Actual distances may vary depending on environmental conditions



1. PortAll
2. Projection Lens
3. Camera
4. LED indicator
5. IR remote sensor
6. Air filter
7. Focus
8. Keypad
9. USB
10. Mini USB vTouch
11. HDMI
12. S video / Composite
13. Audio in/out
14. Dual VGA
15. RS232
16. VGA out
17. Laser module 5V/1.5A
18. LAN
19. Lamp door
20. Kensington® lock slot

Visit Us www.viewsonic.com

SPECIFICATION

Projection system:	0.65" 1080p
Native Resolution:	1920x1080
DC type:	DC3
Brightness:	3300 ANSI Lumens
Contrast Ratio with SuperEco mode:	10000:1
Display Colour:	1.07 Billion Colours
Light Source:	Lamp
Light source life (Nor/SuperEco):	3000/7500
Lamp Watt:	240W
Lens:	F=2.4, f=3.35 mm
Projection Offset:	138%+/-5%
Throw Ratio:	0.22
Image size:	95" - 120"
Throw Distance:	0.12m - 0.25m (100" @ 0.15m)
Keystone:	H:+/-30° , V:+30°/-12°
Optical Zoom:	Fixed
Audible Noise (Eco):	29dB
Resolution Support:	VGA(640 x 480) to WUXGA_RB(1920 x 1200) *RB-Reduced Blanking
HDTV Compatibility:	480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Video Compatibility:	NTSC, PAL, SECAM
Horizontal Frequency:	15K~102KHz
Vertical Scan Rate:	23~120Hz
Interactive Camera:	Yes
Keystone:	H:+/-30° , V:+30°/-12°

INPUT

Computer in (D-SUB 15 pin):	2
Composite:	1
S-video:	1
Audio-in (3.5mm):	1
Audio-in (RCA R/L):	1
HDMI:	1 (Back)
HDMI/MHL:	1 (PortALL)

OUTPUT

Monitor out (D-SUB 15 pin):	1
Audio out (3.5mm):	1
Speaker:	10W Cube x 2
USB type A (Power):	2 (5V2.4A) 1x Back, 1x PortAll

CONTROL

RS232:	1
RJ45:	1
USB type mini B (Services):	2 (1x FW Update/Interactive Camera, 1x Interactive Laser)

OTHERS

Power Supply Voltage:	100-240V+/- 10%, 50/60Hz AC
Power Consumption:	Normal: 410W Standby: <0.5W
Operating Temperature:	0~40℃
Carton:	Brown
Net Weight:	6.1kg
Dimensions (WxDxH) w/adjustment foot:	434x388x153mm
Language:	English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, T-Chinese, S-Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, India, Arabic, Vietnamese

STANDARD ACCESSORY

Power Cord:	1
VGA cable:	1
Remote Control:	1 (w/laser pointer)
QSG & CD:	QSG: 1 / CD: 1
Wall Mount:	1
Interactive Module:	Yes (PJ-vTouch-50S)
Interactive Software:	Yes (vBoard for Windows)

Copyright © ViewSonic Corporation 2000-2018. All rights reserved. (08/07/2018 07:18:20 America/Chicago)