ViewSonic

VIDEO WALL

CDX5552

Key **Features**

Ultra-narrow Bezel | 10x10 Daisy-chain Support with DisplayPort or DVI | Integrated USB Multimedia Player | LAN Control for Remote Content and Display Settings | OPS Slot Compatibility



Product **Description**

The ViewSonic CDX5552 is a 55” (54.6” viewable) commercial display with an ultra-narrow bezel optimized for multi-panel video wall applications. With an edge-to-edge bezel width of only 3.5mm between combined displays, and 10x10 installation via DisplayPort or DVI daisy-chain, the CDX5552 delivers nearly seamless, high-impact video walls for public, retail, and transportation settings. With Full HD 1080p resolution, 500-nit brightness, SuperClear® technology for wide viewing angles, and dual 10W stereo speakers, the CDX5552 delivers sharp, vivid images with incredible sound for superior multimedia performance. What’s more, 3840x2160 resolution is supported in 2x2 daisy-chain configurations for stunning 4K imaging. Free bundled vController and vConfigurator software provides easy maintenance and intuitive interfaces for remote management via a PC or media server. Versatile connectivity options include HDMI, DisplayPort, DVI, CVBS, YPbPr, VGA, RJ45, and RS232 with IR pass-through. A USB port provides simple multimedia playback, while an integrated Intel Open Pluggable Specification (OPS) slot provides easy connectivity to external PCs as well.

Visit Us www.viewsonic.com

LCD PANEL

Panel Size:	55" (54.64")
Type/ Tech:	TFT LCD Module with LED Backlight
Display Area (mm):	1209.6 x 680.4 mm
Aspect Ratio:	16:9
Resolution:	1920x1080
Colors:	1.06 billion colors
Brightness:	500 nits
Contrast Ratio:	1400:1 Typ.
Response Time:	12 ms
Viewing Angles:	178° / 178°
Backlight:	LED Backlight
Backlight Life:	60,000 Hours Typ
Hardness:	Hard coating (3H), Anti-glare treatment

INPUT

HDMI:	x2 (1.4a)
RGB / VGA:	x1
DisplayPort:	x1 (1.2)
DVI:	x1
Audio:	PC audio(3.5 mm) x1, RCA connect x1
CVBS:	x1 (shared with component Y)
YPbPr:	x1
RS232:	x1
IR Pass Through:	x1
OPS:	x1

OUTPUT

DisplayPort:	x1 (1.2)
DVI:	x1
Audio:	RCA connect x1
RS232:	x1
IR Pass Through:	x1

LAN

RJ45:	x1

USB

Type A:	x1 (2.0)

SPEAKERS

10W x2

COMPATIBILITY

RGB PC/HDMI PC:	Up to 1920x1080 @60Hz. Refer to timing table
CVBS:	480i
YPbPr:	480i, 480p,720p,1080i,1080p
DisplayPort:	480i, 480p,720p,1080i,1080p, 4k2k@30Hz
HDMI:	480i, 480p,720p,1080i,1080p, 4k2k@30Hz
DVI:	480i, 480p,720p,1080i,1080p

POWER

Voltage:	100-240 VAC +/- 10% Wide Range, 50-60Hz +/-3 Hz
Consumption:	"On" 185W(typ) "Power Saving" < 0.5 W "Off" (Suspend) < 0.5 W

ERGONOMICS

Wall Mount (VESA):	400 x 400 mm

OPERATING CONDITIONS

Temperature (° C):	5- 40°C (landscape) 5- 35°C (portrait)
Humidity:	20% ~ 80% non-condensing

OPERATING HOUR

24/7

DIMENSIONS

Physical (W x H x D):	1213.4 x 684.2 x 95.0 mm (w/o Stand) 1213.4 x 726.2 x 400 mm (with Stand)

WEIGHT

Net (lb / kg):	29.2 kg (w/o stand) 31.5 kg (with stand)

REGULATIONS

Standard:	CE, CB, WEEE, C-tick, FCC, ICES003, UL/cUL, CE,CB, CU, Energy star 6.0,RoHS, ErP, REACH, PSB, RCM, SASO, EPEAT, UL-MX-CoC,CONUEE

WHAT'S IN THE BOX?

CDX5552 LCD Monitor/ Remote Control with batteries/User manual CD wizard/Quick Start Guide/Power Cables/VGA cable/ RS232 cable/IR sensor cable
*Actual content may differ from market to market

Copyright © ViewSonic Corporation 2000-2018. All rights reserved. (10/03/2018 07:23:30 America/Chicago)