

# ViewSonic® LED DISPLAY XG3202-C

## Key Features

Immersive Viewing Experience with Curved Screen  
| 144Hz Refresh Rate | AMD FreeSync™  
Technology | Low Input Lag | SuperClear VA Panel  
Technology



## Product Description

The ViewSonic® XG3202-C is a 32" (31.5" viewable) 144Hz gaming monitor, featuring 1800R curvature to deliver wide field of view and smooth image performance. Compatible with Free-Sync Technology, this monitor's variable refresh rate capabilities virtually eliminate screen tearing and stuttering for unbelievably fluid gameplay during fast-paced action sequences. This monitor features a 1080p SuperClear® VA panel for enhanced color accuracy and greater viewing angles. Low input lag provides smooth screen performance even in the most graphic-intense sequences. For a game-winning competitive edge, a Game Mode feature optimizes visuals for FPS, RTS and MOBA, let you enjoy better color performance of the game play.

**Visit Us** [www.viewsonic.com](http://www.viewsonic.com)

**LCD**

Type:	32" (16:9)
Panel Technology:	VA(curved 1800R)
Display Area:	31.5"(698.4x392.85)
Optimum Resolution:	1920x1080 (Full HD)
Brightness:	300 cd/m <sup>2</sup> (Typ.)
Contrast Ratio:	3000 :1 (Typ.)
Dynamic Contrast Ratio:	120,000,000 :1
Viewing Angle:	178°(H) / 178° (V)
Response Time:	GTG(avg, scaler OD):6ms(Typ)(ultra fast of user mode)
Panel Surface:	Anti-Glare type, Hard-coating (3H)
Light Source:	30000 Hrs (Min.)
Color Support:	16.7M colors

**INPUT**

Analog:	VGA
Digital:	DVI/HDMI/DisplayPort
Frequency:	Separate Sync
Sync:	Fh = 24 ~ 82 kHz ; Fv = 50 ~ 75 Hz

**COMPATIBILITY**

PC:	1920 x 1080 @60Hz for VGA 1920 x 1080 @144Hz for Dual Link DVI/HDMI/DP
Mac:	1920 x 1080 @60Hz for VGA 1920 x 1080 @144Hz for Dual Link DVI/HDMI/DP

**AUDIO**

Speaker:	2W x2
----------	-------

**CONNECTOR**

Analog:	VGA x1
Digital:	Dual-DVI x1 / HDMI 1.4 x1 / DisplayPort 1.2a x1
Audio in:	3.5mm jack x1
Audio out:	3.5mm jack x1
USB:	USB 2.0 down stream for charging x 1
Power:	Internal Power Board

**POWER**

Voltage:	AC 100-240V (Universal); 50/60 Hz
Consumption:	45W ; Optimize: 38W ; Conserve: 32W
Save mode:	≤0.5 W

**ERGONOMICS**

Tilt:	13° ~ -5°
-------	-----------

**OPERATING CONDITIONS**

Temperature:	32°F to 104°F (0°C to 40°C)
Humidity:	20% to 90% (no condensation)

**DIMENSIONS**

Physical (w/ stand):	721.2 (W) x 495.22 (H) x 230.42 (D) mm
----------------------	---

**WEIGHT**

Net (w/ stand):	8.1kg
-----------------	-------

**REGULATIONS**

CE EMC, CB, RoHS Green BOM & RoHS DoC, ErP, REACH SVHC List & DoC, WEEE, Custom Union, BSMI, RCM, MEPS, KC, e-Standby, CCC, CEL

**WALL MOUNT**

VESA:	100x100mm
-------	-----------

**PACKAGE CONTENTS**

LCD Display / Power Cable / Dual Link DVI Cable/ Audio Cable / Quick Start Guide