VIEWBOARD ACCESSORIES

VB-WIFI-006



Key **Features**

Product **Description**

The ViewSonic® VB-WIFI-006 Wireless Module delivers a faster and more reliable wireless internet connection for ViewBoard and Presentation Display*. It supports tri-frequency bands—2.4GHz, 5GHz, and 6GHz—along with Wi-Fi 6E (802.11ax standard). Ideal for high-bandwidth applications such as video streaming, videoconferencing, and voice calls, it ensures each connected device performs at an optimal level.*Compatible with selected models, please check with your local sales representatives.

Visit Us www.viewsonic.com

WIFI-STANDARD

802.11a/b/g/n/ac/ax

OPERATING FREQUENCY

WIFI: 2.4GHz & 5GHz & 6GHz□
BT: 2.4GHz□AP: 2.4GHz & 5GHz

MODULATION

WIFI:	2.4G : 2412-2484MHz (18.98 dBm) 5G : 5180-5825MHz (13.93dBm) 6G : 5930-7110MHz (15 dBm) *The 6E frequency band varies based on the national regulations for open frequency bands.
BT:	Support 2.1/3.0/4.0/5.3 BLE

POWER

Requirements:	5V/1A
Consumption:	< 5W

DIMENSION

Physical:	224 (L) x 32 (H) x 25 (D) mm/ 8.82 (L) x 1.26 (H) x 0.98 (D) in
Packaging:	447 (L) x 300 (H) x 382 (D) mm/ 17.6 (L) x 11.81 (H) x 15.04 (D) in

WEIGHT

Net:	93g/ 0.21lb
Gross:	113g/ 0.25lb

OPERATING CONDITION

Temperature:	32°F to 104°F (0°C to 40°C)
Humidity:	10% ~ 90% non-condensing

STORAGE / SHIPPING CONDITION

Temperature:	-4°F to 140°F (-20°C to 60°C)
Humidity:	10% ~ 90% non-condensing

COMPLIANCE

NCC,RoHS, DoC

PACKAGE CONTENTS

1. VB-WIFI-006
2. QSG

Copyright © ViewSonic Corporation 2000-2026. All rights reserved.